

B1
At
Cont. 1.
using a configuration variable code book containing a voice source code vector having only a plurality of non-zero amplitude values; and
variably controlling a position of a sample of the non-zero amplitude value in the configuration variable code book using an index and a transmission parameter indicating a feature amount of voice.

2. (Amended) The method according to claim 1, further comprising :

variably controlling the position of the sample of the non-zero amplitude value in the configuration variable code book using the index and a lag value corresponding to a pitch period which is a transmission parameter indicating the feature amount of voice.

3. (Amended) The method according to claim 2, further comprising:

reconstructing the position of the sample of the non-zero amplitude value in the configuration variable code book within a region corresponding to the lag value depending on a relationship between the lag value and a frame length which is a coding unit of the voice.

END B2
4. (Amended) The method according to claim 1, further comprising:

variably controlling the position of the sample of the non-zero amplitude value in the configuration variable code book using the index and a lag value corresponding to a

pitch period which is a transmission parameter indicating the feature amount of voice and a pitch gain value.

5. (Amended) The method according to claim 4, further comprising:

*As
contin.*

reconstructing the position of the sample of the non-zero amplitude value in the configuration variable code book within a region corresponding to the lag value depending on a relationship between the lag value and a frame length which is a coding unit of the voice.

6. (Amended) The method according to claim 5, further comprising:

reconstructing the position of the sample the non-zero amplitude value in the configuration variable code book within a region corresponding to the lag value depending on the pitch gain value.

Two B37

7. (Amended) A voice decoding method for decoding a voice signal coded by a voice coding method based on analysis-by-synthesis vector quantization comprising :

using a configuration variable code book containing a voice source code vector having only a plurality of non-zero amplitude values; and

B3
cancel.

variably controlling a position of a sample of the non- zero amplitude value in the configuration variable code book using an index and a transmission parameter indicating a feature amount of voice.

8. (Amended) The method according to claim 7, further comprising:

A1
contin.

variably controlling the position of the sample of the non-zero amplitude value in the configuration variable code book using the index and a lag value corresponding to a pitch period which is a transmission parameter indicating the feature amount of voice.

9. (Amended) The method according to claim 8, further comprising:

reconstructing the position of the sample of the non-zero amplitude value in the configuration variable code book within a region corresponding to the lag value depending on a relationship between the lag value and a frame length which is a coding unit of the voice.

IND B A

10. (Amended) The method according to claim 7, further comprising:

variably controlling the position of the sample of the non-zero amplitude value in the configuration variable code book using the index and a lag value corresponding to a pitch period which is a transmission parameter indicating the feature amount of voice and a pitch gain value.

11. (Amended) The method according to claim 10, further comprising:

reconstructing the position of the sample of the non-zero amplitude value in the configuration variable code book within a region corresponding to the lag value depending on a relationship between the lag value and a frame length which is a coding unit of the voice.

12. (Amended) The method according to claim 11, further comprising:

reconstructing the position of the sample of the non-zero amplitude value in the configuration variable code book within a region corresponding to the lag value depending on the pitch gain value.

13. (Amended) A voice coding apparatus based on analysis-by-synthesis vector quantization comprising:

a configuration variable code book unit containing a voice source code vector having only a plurality non-zero amplitude values, wherein said configuration variable code book unit variably controls a position of a sample of the non-zero amplitude value in said configuration variable code book unit using an index and a transmission parameter indicating a feature amount of voice.

14. (Amended) The apparatus according to claim 13, wherein:

B5
A1
contin.

said configuration variable code book unit variably controls the position of the sample of the non-zero amplitude value in said configuration variable code book unit using the index and a lag value corresponding to a pitch period which is a transmission parameter indicating the feature amount of voice.

15. (Amended) The apparatus according to claim 13, wherein:

said configuration variable code book unit variably controls the position of the sample of the non-zero amplitude value in said configuration variable code book unit using the index and a lag value corresponding to a pitch period which is a transmission parameter indicating the feature amount of voice and a pitch gain value.

16. (Amended) A voice decoding apparatus for decoding a voice signal coded by a voice coding apparatus based on analysis-by-synthesis vector quantization comprising:

a configuration variable code book unit containing a voice source code vector having only a plurality of non-zero amplitude values, wherein

said configuration variable code book unit variably controls a position of a sample of the non-zero amplitude value using an index and a transmission parameter indicating a feature amount of voice.

17. (Amended) The apparatus according to claim 16, wherein:

B5
A+
concluded

said configuration variable code book unit variably controls the position of the sample of the non-zero amplitude value in said configuration variable code book unit using the index and a lag value corresponding to a pitch period which is a transmission parameter indicating the feature amount of voice.

18. (Amended) The apparatus according to claim 16, wherein:

said configuration variable code book unit variably controls the position of the sample of the non-zero amplitude value in said configuration variable code book unit using the index and a lag value corresponding to a pitch period which is a transmission parameter indicating the feature amount of voice and a pitch gain value.

REMARKS

An Office Action was mailed on January 3, 2002. Claims 1 – 18 are pending in the present application. Claims 1 – 18 are amended. No new matter is introduced.

REJECTIONS UNDER 35 U.S.C. § 102

Claims 1 - 18 are rejected under 35 U.S.C. § 102(b) as being anticipated by U.S. Patent No. 5,701,392 to Adoul et al. Claims 1 - 18 are further rejected under 35 U.S.C. § 102(e) as being anticipated by U.S. Patent No. 5,963,896 to Ozawa. Applicants amend claims 1 – 18 to clarify Applicants' claimed invention, and respectfully traverse these rejections.